



***BUILD TO LIFT,
EFFORTLESSLY!***

INTRODUCING OUR NEW RANGE OF SOLID TYRES

ROCK-XLS

NATURAL RUBBER TREAD

Ensures Optimal Performance & Lifespan

SOFT RESILIO LAYERS WITH Y-LUG DESIGN

Enhanced Shock Absorption Properties



OPTIMAL INTERFERENCE FIT

Secure Fitment

TYRE PERFORMANCE CHARACTERISTICS

Heavy duty loading

01

02

Long Hours Usage

Cut/ Abrasion Resistance

03

04

Heat Resistance

Energy efficeincy

05

06

Driving comfort

ROCK-XLS SIZES

SIZE	RIM WIDTH (inch)	NOMINAL		LOAD CAPACITY IN KG	
		OD (inch)	SW (inch)	LOAD WHEEL	STEER WHEEL
3.00 x 4 (R)/2.10 - 2.50	2.10 - 2.50	9.9	3.3	260	195
3.50 x 4 (R)/2.5	2.5	10	3.5	260	195
4.00 x 4 (R)/2.5	2.5	11.8	3.6	525	410
3.20 - 8 (R)/3	3	8.9	4.05	770	590
4.00 x 8 (R/Y)/3.00 / 3.75	3.00 / 3.75	16	3.9	950	730
5.00 x 8/3.00 / 4.50 / 3.50	3.00/4.50/3.50	17.9	4.9	1420	1090
6.00 x 9/4	4	20.6	5.6	1885	1450
15 x 4 ½ - 8 (125/75 - 8)/3.00 / 3.25	3.00 / 3.25	15.2	4.5	1040	800
16 x 6 - 8 (150/75 - 8)/4.33	4.33	16	6.4	1495	1150
18 x 7 - 8 (180/70 - 8)/4.33	4.33	18	5.9	2145	1650
18 x 9 - 8/7	7	18	8	2300	1900
21 x 8 - 9 (200/75 - 9)/6	6	20.7	7.6	2755	2120
20 x 6 - 9 (S)/4	4	19.45	5.5		
20 x 8 x 9 (S)/6	6	19.45	7.5		
4.00 x 9.75 (R)/3.75	3.75	16.8	4.8		
200 / 50 - 10/6.5	6.5	17.8	7.4	2470	1900
23 x 9 - 10 (225/75 - 10)/6.5	6.5	22.5	8.3	3445	2650
6.50 x 10/5	5	22.7	6.3	2340	1800
6.50 x 10/5.5	5.5	22.7	6.3	2570	1975
7.50 x 10/5.5	5.5	25.7	7.1	3070	2360
560 x 165 x 11/5	5	21.7	6.44		
315 / 45 - 12/10	10	22.7	11	4480	3450
23 x 10 - 12 (250/60 - 12)/8	8	23.3	9.65	3770	2900
7.00 x 12/5	5	25.4	6.9	2920	2240
27 x 10 - 12 (250/75 - 12)/8	8	25.6	9.8	3900	3000
28 x 12.5 x 15 (355/45 - 15)/9.75	9.75	27.1	12.4	5525	4250
32 x 12.1 x 15 (355/65 - 15) (350 - 15)/9.75	9.75	32.28	11.8	7800	6000
250 x 15 (250/70 - 15)/7.00 / 7.50	7.00 / 7.50	28.9	9.3	4750	3650
300 x 15 (315/70 - 15)/8	8	32.3	10.1	5850	4500
400 / 60 - 15/11	11	32.1	12.9	8700	6750
6.00 x 15/4.5	4.5	27.4	5.9	2455	1820
7.00 x 15/5.50 / 6.00 / 6.50	5.50 / 6.00 / 6.50	27.6	7.5	3545	2725

SIZE	RIM WIDTH (inch)	NOMINAL		LOAD CAPACITY IN KG	
		OD (inch)	SW (inch)	LOAD WHEEL	STEER WHEEL
7.50 x 15/5.50 / 6.00 / 6.50	5.50/6.00/6.50	28.3	7.5	3900	3000
8.15 x 15 (225/75 - 15) (28 x 9 - 15)/7	7	27.1	8.4	3445	2650
8.25 x 15/5.50 / 6.50	5.50 / 6.50	30.7	7.9	4750	3650
7.50 x 16/5.50 / 6.00	5.50 / 6.00	30.8	7.9	3908	2831
8.00 x 16/5.5	5.5	30.8	7.9	3965	3050
8.25 x 16/6	6	30.75	8		
7.50 x 20/6	6	34.75	7.05	3840	3200
8.25 x 20/6.50 / 7.00	6.50 / 7.00	38.9	9.1	4400	3675
9.00 x 20/7.00 / 7.50 / 8.00	7.00/7.50/8.00	40.4	9.5	5340	4450
10.00 x 20/7.50 / 8.00	7.50 / 8.00	40.4	9.5	6000	5000
11.00 x 20/7.50 / 8.00	7.50 / 8.00	41.4	10.35	6510	5245
12.00 x 20 - 42/8	8	41.4	10.35	6510	5245
12.00 x 20 - 43/8.00 / 8.50	8.00 / 8.50	43.4	11.6	7500	6250
355 / 50 - 20/10	10	32	12.5	8970	6900
14.00 x 20 (S)/10	10	48.8	13.1	8250	6800
12.00 x 24/8.50 (S) / 10.00 (Y)	8.50 (S)/10.00 (Y)	47	11.8	7980	6650
14.00 x 24/10	10	51.2	13.2	11000	9175

CEAT
SPECIALTY
AGRICULTURE & OTR TYRES

Visit us at [🌐 ceatspecialty.com](https://ceatspecialty.com)
Follow us [f](#) [@](#) [in](#) @ceatspecialtyeurope

