

FLOATMAX VF X3

CEAT
SPECIALTY

FEATURE

Directional pattern gives high protection against aquaplaning, excellent handling.

FEATURE

Big center block at tread center provides to give more traction.

FEATURE

VF flotation tyre provides 40% low inflation pressure improved crop product and efficiency, lower fuel consumption, reduce soil compaction.



LIST OF SIZE

SIZE	LI/SI
VF 560/60R22.5	166D

All tyres conform to ETRTO & TRA standards. Sizes available as of 02/2022.



Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Speed Radius	Load Index	Infl. press.	maximum load, kg (lbs)					
		SW	OD	Radius		Index			Speed, km/h (mph)					
		mm	mm	mm	mm	(SRI)	Speed	bar	MIXED APPLICATION					
		in	in	in	in		Symbol	psi	10	20	30	40	50	65
VF 560/ 60R22.5	AG16.00							0.8	3740	3470	3170	2940	2670	2280
								12	8240	7640	6980	6480	5880	5020
								1.4	5360	4970	4550	4220	3830	3270
		556	1250	537	3731	575	166D	20	11810	10950	10020	9300	8440	7200
		21.9	49.2	21.1	146.9			2	6610	6130	5600	5200	4720	4030
								29	14560	13500	12330	11450	10400	8880
								2.6	7690	7130	6520	6050	5490	4690
								38	16940	15700	14360	13330	12090	10330
								3.2	8690	8060	7370	6840	6200	5300
								46	19140	17750	16230	15070	13660	11670

All tires confirms ETRTO T&RA & STRO standards

