

TYROCK

CEAT
SPECIALTY

WITH THE POWER OF CTR*

FEATURE

Traction pattern

BENEFIT

Suitable for front wheel
of back hoe loader

FEATURE

Wider lug

BENEFIT

Engineered to provide
excellent traction



FEATURE

Special Industrial
tread compound

BENEFIT

Resistant to
tearing & cutting

FEATURE

Tough nylon casing

BENEFIT

High load
carrying capacity



LIST OF SIZES

SIZE	L/SS
12.5/80-18 12 PR	129 A8
12.5/80-18 12 PR	132 A8
12.5/80-18 14 PR	138 A8

All tyres conform to ETRTO & TRA standards. Sizes available as of 10/2021.



Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Tread Depth	Infl. Prs.	Load Capacity		No. of lugs
				mm	mm	mm	mm	mm	bar	Load Index Speed Symbol	Max Load	
				in	in	in	in	32nds	psi		kg lbs	
12.5/80-18	12	TL	9.0	308	988	465	2900	25	3.7	129 A8	1850	20
				39	12	18	114	31	54		4080	

All tyres conform to T & RA and ETRTO Standards

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circum.	Load Index	Infl. Press.	Recommended load, kg (lbs)											
		SW	OD	mm	mm			Speed	bar	Free Rolling						Drive wheel			
		mm	mm	mm	mm	Symbol	psi			10	20	22	25	30	40	10	20	25	30
12.5/80-18	9.00	308	988	465	2900	138A8(DW)	5.5	4690	4220	4200	3990	3750	3350	3305	2975	2810	2640	2360	
		12.1	38.9	18.3	114.2			18PR TT	80	10340	9300	9260	8790	8270	7380	7280	6560	6190	5820

All tyres conform to T & RA and ETRTO Standards

Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Tread Depth	RCI	Infl. Prs.	Load Capacity		No. of lugs
				mm	mm	mm	mm	mm		bar	Load Index Speed Symbol	Max Load	
				in	in	in	in	32nds		psi		kg lbs	
12.5/80-18	12	TL	9.0	308	988	465	2900	25	34	3.75	129 A8	1850	20
				39	12	18	114	31		54		4080	
12.5/80-18	14	TL	9.0	308	988	465	2900	25	34	4.3	132 A8	2000	20
				39	12	18	114	31		62		4410	

All tyres conform to T & RA and ETRTO Standards

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circum.	Weight	Load Index	Lugs	Infl. Press.	Recommended load, kg (lbs)							
		SW	OD	mm	mm					kg	Speed	Drive wheel					
		mm	mm	mm	mm	lbs	Symbol	bar		Static	10	15	20	25	30	40	
12.5/80-18 IND	9.00	308	988	465	2900	44.5	14PR TL	20	1	2000	1190	1130	1070	1010	950	850	
									1.2	2230	1330	1260	1200	1130	1060	950	
		1.4	2440	1460	1380	1310	1240		1160	1040							
		1.6	2630	1570	1490	1410	1330		1250	1120							
		1.8	2820	1680	1600	1510	1430		1340	1200							
		2	3010	1790	1700	1610	1520		1430	1280							
		2.4	3340	1990	1890	1790	1690		1590	1420							
		2.6	3500	2090	1980	1880	1770		1670	1490							
		2.8	3670	2180	2070	1970	1860		1750	1560							
		3	3810	2270	2150	2040	1930		1810	1620							
		3.2	3950	2350	2230	2120	2000		1880	1680							
		3.4	4090	2440	2310	2190	2070		1950	1740							
		3.6	4230	2520	2390	2270	2140		2020	1800							
		3.8	4370	2600	2470	2340	2210		2080	1860							
		4	4510	2690	2550	2420	2280		2150	1920							
		4.3	4700	2800	2660	2520	2380		2240	2000							

All tyres conform to T & RA and ETRTO Standards

