

FEATURES AND BENEFITS

Extra thick sidewall

Improves sidewall stability and prevents accidental damages



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



ELEVETA PLUS

Size	Type	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in			bar	kmph	kg
9.00-20 NHS	TT	14	7.0X20	260	1040	468	2998	6.9	15	5805
				10.2	40.9	18.4	118	100	10	12795
10.00-20 NHS	TT	16	7.0X20	285	1075	480	3125	7.9	15	6700
				11.2	42.3	18.8	123.1	115	10	14770
12.00-20 NHS	TT	20	8.5X20	315	1155	515	3305	8.95	15	9000
				12.4	45.5	20.2	130.1	130	10	19840
12.00-20 NHS	TT	28	8.5X20	315	1155	515	3305	10	15	9640
				12.4	45.5	20.2	130.1	145	10	19840