

FEATURES AND BENEFITS

Extra thick sidewall

Improves sidewall stability and prevents accidental damages



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



ELEVETA X3

Size	Type	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity				
				SW	OD			Infl. Pre	Max. Speed	Max Load	Max. Speed	Max Load
				mm/in	mm/in							
								psi	mph	lbs	mph	lbs
7.00-12 NHS	TT	12	5.00	192	672	316	1956	8.5	25	2678	25	2060
				7.6	26.5	12.4	77.0	123	15	5905	15	4542
6.50-10 NHS	TT	12	5.00	177	588	276	1711	9	25	2145	25	1650
				7.0	23.1	10.9	67.4	131	15	4730	15	3638
6.00-9 NHS	TT	10	4.00	160	540	254	1571	8.5	25	1716	25	1320
				6.3	21.3	10.0	61.9	123	15	3784	15	2911
28X9-15 (8.15-15) NHS	TT	14	7.00	216	707	332	2057	10	25	3900	25	3000
				8.5	27.8	13.1	81.0	145	15	8600	15	6615
8.25-15 NHS	TT	14	6.50	234	836	393	2433	8	25	4225	25	3250
				9.2	32.9	15.5	95.8	116	15	9316	15	7166