

FEATURES AND BENEFITS

R1-W tread depth
Longer tire life



Higher angle and lug
overlap at centre
Better roadability



Wider tread
larger inner volume
Reduced soil
compaction



Rounded shoulder
Lesser damage to
soil and crop



Lower angle at
shoulder
Superior traction



*CTR-Low Compaction, High Traction, High Roadability

FARMAX R85
WITH THE POWER OF CTR*



FARMAX R85

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	
420/85 R34	W15L W14L W13	450 17.7	1578 62.1	724 28.5	4705 185.3	142D/ 145A8	Speed	bar	Static	10	20	30	40	50	65
							Symbol			psi	6	12	19	25	31
							0.8	4440	2900	2370	2220	2110	2030	1930	
							12	9780	6390	5220	4890	4250	4470	4250	
							1.2	5010	3270	2680	2510	2390	2290	2180	
							17	11040	7200	5900	5530	4800	5040	4800	
							1.4	5570	3630	2980	2780	2650	2540	2420	
							20	12270	8000	6560	6120	5330	5590	5330	
1.6	6100	3980	3260	3050	2900	2780	2650								
23	13440	8770	7180	6720	6390	6120	5840								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	mm/in	mm/in		
340/85 R24	W12 W11	355 14	1188 46.8	542 21.3	3528 138.9	125 D 128A8	Speed	bar	Static	10	20	30	40	50	65
							Symbol			psi	6	12	19	25	31
							0.8	2390	1560	1280	1200	1140	1090	1040	
							12	5260	3440	2820	2640	2290	2400	2290	
							1	2740	1790	1460	1370	1300	1250	1190	
							15	6040	3940	3220	3020	2620	2750	2620	
							1.3	3240	2120	1730	1620	1540	1480	1410	
							19	7140	4670	3810	3570	3110	3260	3110	
1.6	3800	2480	2030	1900	1810	1730	1650								
23	8370	5460	4470	4190	3990	3810	3630								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	mm/in	mm/in		
520/85 R42	DW16L DW18 L	530 20.9	1951 76.8	889 35.0	5791 228.0	169D / 172A8	Speed	bar	Static	10	20	30	40	50	65
							Symbol			psi	6	12	19	25	31
							0.8	5980	3900	3200	2990	2850	2730	2600	
							12	13170	8590	7050	6590	5730	6010	5730	
							1	6810	4440	3640	3400	3240	3110	2960	
							15	15000	9780	8020	7490	6520	6850	6520	
							2	10280	6710	5500	5140	4890	4690	4470	
							29	22640	14780	12110	11320	9850	10330	9850	
							2.8	12010	7830	6420	6000	5720	5480	5220	
							41	26450	17250	14140	13220	11500	12070	11500	
							3.4	13340	8700	7130	6670	6350	6090	5800	
49	29380	19160	15700	14690	13990	13410	12780								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
mm/in	mm/in	mm/in	mm/in	Symbol	psi	6	12	19	25	31	40			
380/85 R24	W12 W13 W11	385 15.2	1260 49.6	571 22.5	3728 146.8	131D / 134A8	0.8	2850	1860	1530	1430	1360	1300	1240
							12	6280	4100	3370	3150	2730	2860	2730
							1	3240	2120	1730	1620	1540	1480	1410
							15	7140	4670	3810	3570	3110	3260	3110
							1.3	3860	2520	2070	1930	1840	1760	1680
							19	8500	5550	4560	4250	3700	3880	3700
							1.6	4490	2930	2400	2240	2140	2050	1950
							23	9890	6450	5290	4930	4710	4520	4300

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
mm/in	mm/in	mm/in	mm/in	Symbol	psi	6	12	19	25	31	40			
380/85 R28	W12 W13 W11	390 15.4	1357 53.4	620 24.4	4035 158.9	133D / 136 A8	0.8	3060	2000	1640	1530	1460	1400	1330
							12	6740	4410	3610	3370	2930	3080	2930
							1	3500	2280	1870	1750	1660	1600	1520
							15	7710	5020	4120	3850	3350	3520	3350
							1.3	4140	2700	2210	2070	1970	1890	1800
							19	9120	5950	4870	4560	3960	4160	3960
							1.6	4740	3090	2530	2370	2260	2160	2060
							23	10440	6810	5570	5220	4980	4760	4540

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
mm/in	mm/in	mm/in	mm/in	Symbol	psi	6	12	19	25	31	40			
420/85 R30	W15L W14L W13	450 17.7	1476 58.1	673 26.5	4385 172.6	140 D / 143 A8	0.8	3680	2400	1970	1840	1750	1680	1600
							12	8110	5290	4340	4050	3520	3700	3520
							1	4190	2730	2240	2090	1990	1910	1820
							15	9230	6010	4930	4600	4010	4210	4010
							1.3	4990	3260	2670	2500	2380	2280	2170
							19	10990	7180	5880	5510	4780	5020	4780
							1.6	5750	3750	3080	2880	2740	2630	2500
							23	12670	8260	6780	6340	6040	5790	5510

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
		mm/in	mm/in						6	12	19	25	31	40	
420/85 R34	W15L W14L W13	450 17.7	1578 62.13	725 28.5	4705 185.2	147D/ 150A8	0.8	3910	2550	2090	1960	1860	1790	1700	
							12	8610	5620	4600	4320	4100	3940	3740	
							1.4	5590	3650	2990	2790	2660	2550	2430	
							20	12310	8040	6590	6150	5860	5620	5350	
							2	6670	4350	3570	3340	3180	3050	2900	
							29	14690	9580	7860	7360	7000	6720	6390	
							2.4	7070	4610	3780	3540	3370	3230	3075	
							35	15570	10150	8330	7800	7420	7110	6770	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
		mm/in	mm/in						6	12	19	25	31	40	
460/85 R38	W16L W15L W14L	480 18.9	1747 68.8	796 31.3	5214 205.3	149D/ 152A8	0.8	4740	3090	2530	2370	2260	2160	2060	
							12	10440	6810	5570	5220	4980	4760	4540	
							1.2	6100	3980	3260	3050	2900	2780	2650	
							17	13440	8770	7180	6720	6390	6120	5840	
							1.4	6670	4350	3570	3340	3180	3050	2900	
							20	14690	9580	7860	7360	7000	6720	6390	
							1.6	7480	4880	4000	3740	3560	3410	3250	
							23	16480	10750	8810	8240	7840	7510	7160	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
		mm/in	mm/in						6	12	19	25	31	40	
460/85 R38	W16L W15L W14L	480 18.9	1747 68.8	796 31.3	5214 205.3	153D/ 156A8	0.8	4990	3260	2670	2500	2380	2280	2170	
							12	10990	7180	5880	5510	5240	5020	4780	
							1.2	6330	4130	3380	3160	3010	2890	2750	
							17	13940	9100	7440	6960	6630	6370	6060	
							1.6	7480	4880	4000	3740	3560	3410	3250	
							23	16480	10750	8810	8240	7840	7510	7160	
							2.4	8400	5480	4490	4200	4000	3830	3650	
							35	18500	12070	9890	9250	8810	8440	8040	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
		mm/in	mm/in						6	12	19	25	31	40	
460/85 R38	W16L W15L W14L	480 18.9	1747 68.8	796 31.3	5214 205.3	167D/ 170A8	0.8	4990	3260	2670	2500	2380	2280	2170	
							12	10990	7180	5880	5510	5240	5020	4780	
							2.8	9430	6150	5040	4720	4490	4310	4100	
							41	20770	13550	11100	10400	9890	9490	9030	
							3.6	10930	7130	5840	5460	5200	4990	4750	
							52	24070	15700	12860	12030	11450	10990	10460	
							4.4	12540	8180	6700	6270	5970	5720	5450	
							64	27620	18020	14760	13810	13150	12600	12000	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
280/85 R24	W10 W9	285 11.22	1086 42.76	496 19.52	3235 127.4	115D/ 118A8	0.8	1840	1200	980	920	880	840	800
							12	4050	2640	2160	2030	1940	1850	1760
							1.2	2350	1530	1250	1170	1120	1070	1020
							17	5180	3370	2750	2580	2470	2360	2250
							1.4	2580	1680	1380	1290	1230	1180	1120
							20	5680	3700	3040	2840	2710	2600	2470
							1.6	2790	1820	1490	1400	1330	1280	1215
							23	6150	4010	3280	3080	2930	2820	2680

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
380/85 R30	W12 W13 W11	385 15.16	1408 55.43	646 25.42	4195 165.2	135D/ 138A8	0.8	3130	2040	1670	1560	1490	1430	1360
							12	6890	4490	3680	3440	3280	3150	3000
							1.2	4030	2630	2150	2010	1920	1840	1750
							17	8880	5790	4740	4430	4230	4050	3850
							1.4	4490	2930	2400	2240	2140	2050	1950
							20	9890	6450	5290	4930	4710	4520	4300
							1.6	5010	3270	2680	2510	2390	2290	2180
							23	11040	7200	5900	5530	5260	5040	4800

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
280/85 R28	W10 W9	285 11.22	1187 46.73	546 21.51	3552 139.8	118D/ 121A8	0.8	1900	1240	1010	950	900	870	825
							12	4190	2730	2220	2090	1980	1920	1820
							1.2	2440	1590	1300	1220	1160	1110	1060
							17	5370	3500	2860	2690	2560	2440	2330
							1.4	2710	1770	1450	1360	1290	1240	1180
							20	5970	3900	3190	3000	2840	2730	2600
							1.6	3040	1980	1620	1520	1450	1390	1320
							23	6700	4360	3570	3350	3190	3060	2910

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
420/85 R24	W12 W13 W11	450 17.72	1324 52.13	597 23.52	3906 153.8	137D/ 140A8	0.8	3340	2180	1780	1670	1590	1520	1450
							12	7360	4800	3920	3680	3500	3350	3190
							1.2	4260	2780	2280	2130	2030	1940	1850
							17	9380	6120	5020	4690	4470	4270	4070
							1.4	4740	3090	2530	2370	2260	2160	2060
							20	10440	6810	5570	5220	4980	4760	4540
							1.6	5290	3450	2830	2650	2520	2420	2300
							23	11650	7600	6230	5840	5550	5330	5070

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19
420/85 R30	W16L W15L W14L	450 17.72	1476 58.11	673 26.51	4385 172.6	147D/ 150A8	0.8	3840	2510	2050	1920	1830	1750	1670	
							12	8460	5530	4520	4230	4030	3850	3680	
							1.6	5750	3750	3080	2880	2740	2630	2500	
							23	12670	8260	6780	6340	6040	5790	5510	
							2	6280	4100	3360	3140	2990	2870	2730	
							29	13830	9030	7400	6920	6590	6320	6010	
							2.4	7070	4610	3780	3540	3370	3230	3075	
							35	15570	10150	8330	7800	7420	7110	6770	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19
280/85 R20	W10 W9	285 11.22	984 38.74	445 17.51	2914 114.7	112D/ 115A8	0.8	1730	1130	920	860	820	790	750	
							12	3810	2490	2030	1890	1810	1740	1650	
							1.2	2190	1430	1170	1090	1040	1000	950	
							17	4820	3150	2580	2400	2290	2200	2090	
							1.4	2390	1560	1280	1200	1140	1090	1040	
							20	5260	3440	2820	2640	2510	2400	2290	
							1.6	2580	1680	1380	1290	1230	1180	1120	
							23	5680	3700	3040	2840	2710	2600	2470	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19
320/85 R24	W11 W10 W9	325 12.80	1154 45.43	523 20.59	3426 134.9	122D/ 125A8	0.8	2210	1440	1180	1100	1050	1010	960	
							12	4870	3170	2600	2420	2310	2220	2110	
							1.2	2810	1830	1500	1400	1340	1280	1220	
							17	6190	4030	3300	3080	2950	2820	2690	
							1.4	3200	2090	1710	1600	1520	1460	1390	
							20	7050	4600	3770	3520	3350	3220	3060	
							1.6	3450	2250	1850	1730	1640	1580	1500	
							23	7600	4960	4070	3810	3610	3480	3300	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19
320/85 R24	W11 W10 W9	325 12.80	1154 45.43	523 20.59	3426 134.9	142D/ 145A8	0.8	2160	1410	1160	1080	1030	990	940	
							12	4760	3110	2560	2380	2270	2180	2070	
							2.2	3910	2550	2090	1960	1860	1790	1700	
							32	8610	5620	4600	4320	4100	3940	3740	
							3.2	4740	3090	2530	2370	2260	2160	2060	
							46	10440	6810	5570	5220	4980	4760	4540	
							4.2	6100	3980	3260	3050	2900	2780	2650	
							61	13440	8770	7180	6720	6390	6120	5840	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
250/85 R24	W8 W7 W9	250 9.8	1036 40.8	477 18.8	3030 121.9	109D/ 112A8	0.8	1590	1040	850	790	760	720	690	
							12	3500	2290	1870	1740	1670	1590	1520	
							1.2	2000	1310	1070	1000	950	910	870	
							17	4410	2890	2360	2200	2090	2000	1920	
							1.4	2190	1430	1170	1090	1040	1000	950	
							20	4820	3150	2580	2400	2290	2200	2090	
							1.6	2370	1550	1270	1180	1130	1080	1030	
							23	5220	3410	2800	2600	2490	2380	2270	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
460/85 R34	W16L W15L W14L	480 18.90	1646 64.80	752 29.62	4895 192.7	147D 150A8	0.8	4490	2930	2400	2240	2140	2050	1950	
							12	9890	6450	5290	4930	4710	4520	4300	
							1.2	5750	3750	3080	2880	2740	2630	2500	
							17	12670	8260	6780	6340	6040	5790	5510	
							1.4	6530	4260	3490	3270	3110	2980	2840	
							20	14380	9380	7690	7200	6850	6560	6260	
							1.6	7070	4610	3780	3540	3370	3230	3075	
							23	15570	10150	8330	7800	7420	7110	6770	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
460/85 R34	W16L W15L W14L	480 18.90	1646 64.80	752 29.62	4895 192.7	157D 160A8	0.8	4490	2930	2400	2240	2140	2050	1950	
							12	9890	6450	5290	4930	4710	4520	4300	
							2.2	7910	5160	4230	3960	3770	3610	3440	
							32	17420	11370	9320	8720	8300	7950	7580	
							2.8	9110	5940	4870	4550	4340	4160	3960	
							41	20070	13080	10730	10020	9560	9160	8720	
							3	9490	6190	5070	4740	4520	4330	4125	
							44	20900	13630	11170	10440	9960	9540	9090	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
460/85 R30	W16L W15L W14L	480 18.90	1544 60.79	701 27.61	4574 180.1	145D 148A8	0.8	4260	2780	2280	2130	2030	1940	1850	
							12	9380	6120	5020	4690	4470	4270	4070	
							1.2	5430	3540	2900	2710	2580	2480	2360	
							17	11960	7800	6390	5970	5680	5460	5200	
							1.4	6160	4020	3300	3080	2930	2810	2680	
							20	13570	8850	7270	6780	6450	6190	5900	
							1.6	6670	4350	3570	3340	3180	3050	2900	
							23	14690	9580	7860	7360	7000	6720	6390	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
320/85 R20	W10 W11 W9	320 12.60	1052 41.42	472 18.59	3102 122.1	119D/ 122A8	0.8	2090	1370	1120	1050	1000	960	910	
							12	4600	3020	2470	2310	2200	2110	2000	
							1.2	2650	1730	1410	1320	1260	1210	1150	
							17	5840	3810	3110	2910	2780	2670	2530	
							1.4	2900	1890	1550	1450	1380	1320	1260	
							20	6390	4160	3410	3190	3040	2910	2780	
							1.6	3130	2040	1670	1560	1490	1430	1360	
							23	6890	4490	3680	3440	3280	3150	3000	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
380/85 R34	W12 W13 W11	385 15.16	1510 59.45	697 27.43	4516 177.8	137D / 140A8	0.8	3340	2180	1780	1670	1590	1520	1450	
							12	7360	4800	3920	3680	3500	3350	3190	
							1.2	4490	2930	2400	2240	2140	2050	1950	
							17	9890	6450	5290	4930	4710	4520	4300	
							1.4	4900	3200	2620	2450	2330	2240	2130	
							20	10790	7050	5770	5400	5130	4930	4690	
							1.6	5290	3450	2830	2650	2520	2420	2300	
							23	11650	7600	6230	5840	5550	5330	5070	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
520/85 R38	DW16 DW18L	530 20.87	1855 73.03	847 33.34	5513 217.0	155D/ 158A8	0.8	5660	3690	3030	2830	2690	2580	2460	
							12	12470	8130	6670	6230	5930	5680	5420	
							1	6440	4200	3440	3220	3070	2940	2800	
							15	14190	9250	7580	7090	6760	6480	6170	
							1.4	8170	5330	4370	4080	3890	3730	3550	
							20	18000	11740	9630	8990	8570	8220	7820	
							1.6	8910	5810	4770	4460	4240	4070	3875	
							23	19630	12800	10510	9820	9340	8960	8540	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65	
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40	
520/85 R38	DW16 DW18L	530 20.87	1855 73.03	847 33.34	5513 217.0	169D/ 172A8	0.8	5660	3690	3030	2830	2690	2580	2460	
							12	12470	8130	6670	6230	5930	5680	5420	
							1.8	9490	6190	5070	4740	4520	4330	4125	
							26	20900	13630	11170	10440	9960	9540	9090	
							2.6	10930	7130	5840	5460	5200	4990	4750	
							38	24070	15700	12860	12030	11450	10990	10460	
							3.6	13340	8700	7130	6670	6350	6090	5800	
							52	29380	19160	15700	14690	13990	13410	12780	

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40
520/85 R46	DW16L	530 20.87	2052 80.79	938 36.93	6253 246.2	174D / 177A8	0.8	6280	4100	3360	3140	2990	2870	2730
							12	13830	9030	7400	6920	6590	6320	6010
							2.2	11210	7310	6000	5610	5340	5120	4875
							32	24690	16100	13220	12360	11760	11280	10740
							3.2	13340	8700	7130	6670	6350	6090	5800
							46	29380	19160	15700	14690	13990	13410	12780
							4	15410	10050	8240	7710	7340	7040	6700
							58	33940	22140	18150	16980	16170	15510	14760

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40
520/85 R46	DW16L	530 20.87	2052 80.79	938 36.93	6253 246.2	158D / 161A8	0.8	6280	4100	3360	3140	2990	2870	2730
							12	13830	9030	7400	6920	6590	6320	6010
							1	7070	4610	3780	3540	3370	3230	3075
							15	15570	10150	8330	7800	7420	7110	6770
							1.3	8400	5480	4490	4200	4000	3830	3650
							19	18500	12070	9890	9250	8810	8440	8040
							1.6	9780	6380	5230	4890	4650	4460	4250
							23	21540	14050	11520	10770	10240	9820	9360

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40
420/85 R38	W15L W14L W13	450 17.72	1680 66.14	775 30.53	5026 197.9	144D/ 147A8	0.8	4300	2810	2300	2150	2050	1960	1870
							12	9470	6190	5070	4740	4520	4320	4120
							1	4900	3200	2620	2450	2330	2240	2130
							15	10790	7050	5770	5400	5130	4930	4690
							1.3	5700	3720	3050	2850	2720	2600	2480
							19	12560	8190	6720	6280	5990	5730	5460
							1.6	6440	4200	3440	3220	3070	2940	2800
							23	14190	9250	7580	7090	6760	6480	6170

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	10	20	30	40	50	65
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	12	19	25	31	40
520/85 R42	DW16L	530 20.87	1951 76.81	888 34.94	5945 234.1	157D/ 160A8	0.8	5920	3860	3170	2960	2820	2700	2575
							12	13040	8500	6980	6520	6210	5950	5670
							1	6900	4500	3690	3450	3290	3150	3000
							15	15200	9910	8130	7600	7250	6940	6610
							1.3	8170	5330	4370	4080	3890	3730	3550
							19	18000	11740	9630	8990	8570	8220	7820
							1.6	9490	6190	5070	4740	4520	4330	4125
							23	20900	13630	11170	10440	9960	9540	9090

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
					Symbol	psi		6	12	19	25	31	40	
320/85 R38	W11 W10 W9	325 12.80	1509 59.41	701 27.59	4598 181.0	143D/ 146A8	0.8	2600	1700	1390	1300	1240	1190	1130
							12	5730	3740	3060	2860	2730	2620	2490
							1.8	4160	2720	2230	2080	1980	1900	1810
							26	9160	5990	4910	4580	4360	4190	3990
							2.6	5180	3380	2770	2590	2460	2360	2250
							38	11410	7440	6100	5700	5420	5200	4960
							3.6	6270	4090	3350	3130	2980	2860	2725
							52	13810	9010	7380	6890	6560	6300	6000

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
					Symbol	psi		6	12	19	25	31	40	
320/85 R32	W11 W10 W9	325 12.80	1357 53.43	625 24.59	4063 160.0	126D/ 129A8	0.8	2650	1730	1410	1320	1260	1210	1150
							12	5840	3810	3110	2910	2780	2670	2530
							1	2880	1880	1540	1440	1370	1310	1250
							15	6340	4140	3390	3170	3020	2890	2750
							1.3	3470	2270	1860	1740	1650	1590	1510
							19	7640	5000	4100	3830	3630	3500	3330
							1.6	3910	2550	2090	1960	1860	1790	1700
							23	8610	5620	4600	4320	4100	3940	3740

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
					Symbol	psi		6	12	19	25	31	40	
320/85 R32	W11 W10 W9	325 12.80	325 12.80	325 12.80	325 12.80	142D/ 145A8	0.8	2550	1670	1370	1280	1220	1170	1110
							12	5620	3680	3020	2820	2690	2580	2440
							2.2	4300	2810	2300	2150	2050	1960	1870
							32	9470	6190	5070	4740	4520	4320	4120
							3.2	5360	3500	2870	2680	2550	2450	2330
							46	11810	7710	6320	5900	5620	5400	5130
							4	6100	3980	3260	3050	2900	2780	2650
							58	13440	8770	7180	6720	6390	6120	5840

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
					Symbol	psi		6	12	19	25	31	40	
320/85 R32	W11 W10 W9	325 12.80	1357 53.43	625 24.59	4063 160.0	145D/ 148A8	0.8	2550	1670	1370	1280	1220	1170	1110
							12	5620	3680	3020	2820	2690	2580	2440
							2	4210	2750	2250	2100	2000	1920	1830
							29	9270	6060	4960	4630	4410	4230	4030
							3	5340	3480	2850	2670	2540	2440	2320
							44	11760	7670	6280	5880	5590	5370	5110
							4.4	6670	4350	3570	3340	3180	3050	2900
							64	14690	9580	7860	7360	7000	6720	6390

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20	30
Symbol	psi	6	12	19	25	31	40								
340/85 R38	W12	355	1543	719	4646	133D/ 135A8	0.8	2960	1930	1580	1480	1410	1350	1285	
							12	6520	4250	3480	3260	3110	2970	2830	
	W11	13.98	60.75	28.32	182.9	1	3450	2250	1850	1730	1640	1580	1500		
						15	7600	4960	4070	3810	3610	3480	3300		
	1.3	4190	2730	2240	2090	1990	1910	1820							
	19	9230	6010	4930	4600	4380	4210	4010							
	1.6	4740	3090	2530	2370	2260	2160	2060							
	23	10440	6810	5570	5220	4980	4760	4540							

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20	30
Symbol	psi	6	12	19	25	31	40								
340/85 R38	W12	355	1543	719	4646	148D/ 151A8	0.8	3060	2000	1640	1530	1460	1400	1330	
							12	6740	4410	3610	3370	3220	3080	2930	
	W11	13.98	60.75	28.32	182.9	2.2	5110	3330	2730	2550	2430	2330	2220		
						32	11260	7330	6010	5620	5350	5130	4890		
	3.2	6350	4140	3390	3170	3020	2900	2760							
	46	13990	9120	7470	6980	6650	6390	6080							
	4	7250	4730	3870	3620	3450	3310	3150							
	58	15970	10420	8520	7970	7600	7290	6940							

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20	30
Symbol	psi	6	12	19	25	31	40								
340/85 R38	W12	355	1543	719	4646	151D/ 154A8	0.8	2960	1930	1580	1480	1410	1350	1285	
							12	6520	4250	3480	3260	3110	2970	2830	
	W11	13.98	60.75	28.32	182.9	2	5150	3360	2760	2580	2450	2350	2240		
						29	11340	7400	6080	5680	5400	5180	4930		
	3	6260	4080	3350	3130	2980	2860	2720							
	44	13790	8990	7380	6890	6560	6300	5990							
	4.5	7940	5180	4240	3970	3780	3620	3450							
	65	17490	11410	9340	8740	8330	7970	7600							

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20	30
Symbol	psi	6	12	19	25	31	40								
320/85 R28	W11	330	1255	574	3698	124D/ 127A8	0.8	2480	1620	1330	1240	1180	1130	1080	
							12	5460	3570	2930	2730	2600	2490	2380	
	W10	12.99	49.41	22.58	145.6	1	2810	1830	1500	1400	1340	1280	1220		
						15	6190	4030	3300	3080	2950	2820	2690		
	1.3	3270	2130	1750	1630	1550	1490	1420							
	19	7200	4690	3850	3590	3410	3280	3130							
	1.6	3680	2400	1970	1840	1750	1680	1600							
	23	8110	5290	4340	4050	3850	3700	3520							

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
Symbol	psi	6	12	19	25	31	40							
320/85 R34	W11 W10 W9	325 12.80	1408 55.43	650 25.59	4215 166.0	141D / 144A8	0.8	2580	1680	1380	1290	1230	1180	1120
							12	5680	3700	3040	2840	2710	2600	2470
							1.8	4260	2780	2280	2130	2030	1940	1850
							26	9380	6120	5020	4690	4470	4270	4070
							2.7	5150	3360	2760	2580	2450	2350	2240
							39	11340	7400	6080	5680	5400	5180	4930
							3.6	5920	3860	3170	2960	2820	2700	2575
							52	13040	8500	6980	6520	6210	5950	5670

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
Symbol	psi	6	12	19	25	31	40							
340/85 R36	W12 W11	355 13.98	1492 58.74	694 27.32	4486 176.6	132D/ 135A8	0.8	2880	1880	1540	1440	1370	1310	1250
							12	6340	4140	3390	3170	3020	2890	2750
							1	3340	2180	1780	1670	1590	1520	1450
							15	7360	4800	3920	3680	3500	3350	3190
							1.3	3910	2550	2090	1960	1860	1790	1700
							19	8610	5620	4600	4320	4100	3940	3740
							1.6	4600	3000	2460	2300	2190	2100	2000
							23	10130	6610	5420	5070	4820	4630	4410

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
Symbol	psi	6	12	19	25	31	40							
320/85 R36	W11 W10 W9	325 12.80	1458 57.40	675 26.59	4380 172.4	128D/ 131A8	0.8	2740	1790	1460	1370	1300	1250	1190
							12	6040	3940	3220	3020	2860	2750	2620
							1	3130	2040	1670	1560	1490	1430	1360
							15	6890	4490	3680	3440	3280	3150	3000
							1.3	3660	2390	1960	1830	1740	1670	1590
							19	8060	5260	4320	4030	3830	3680	3500
							1.6	4140	2700	2210	2070	1970	1890	1800
							23	9120	5950	4870	4560	4340	4160	3960

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
Symbol	psi	6	12	19	25	31	40							
250/85 R28	W8 W7 W9	250 9.84	1137 44.76	526 20.72	3329 131.1	112D/ 115A8	0.8	1610	1050	860	810	770	740	700
							12	3550	2310	1890	1780	1700	1630	1540
							1	1840	1200	980	920	880	840	800
							15	4050	2640	2160	2030	1940	1850	1760
							1.3	2280	1490	1220	1140	1080	1040	990
							19	5020	3280	2690	2510	2380	2290	2180
							1.6	2580	1680	1380	1290	1230	1180	1120
							23	5680	3700	3040	2840	2710	2600	2470

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31		40	
250/85 R20	W8 W7 W9	250 9.84	933 36.73	424 16.71	2755 108.5	116D / 119A8	0.8	1380	900	740	690	660	630	600
							12	3040	1980	1630	1520	1450	1390	1320
							1.4	1960	1280	1050	980	930	890	850
							20	4320	2820	2310	2160	2050	1960	1870
							2	2580	1680	1380	1290	1230	1180	1120
							29	5680	3700	3040	2840	2710	2600	2470
							2.4	2880	1880	1540	1440	1370	1310	1250
							35	6340	4140	3390	3170	3020	2890	2750

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31		40	
340/85 R28	W12 W11	355 13.98	1289 50.75	592 23.32	3847 151.5	127D/ 130A8	0.8	2690	1760	1440	1350	1280	1230	1170
							12	5930	3880	3170	2970	2820	2710	2580
							1	3060	2000	1640	1530	1460	1400	1330
							15	6740	4410	3610	3370	3220	3080	2930
							1.3	3570	2330	1910	1780	1700	1630	1550
							19	7860	5130	4210	3920	3740	3590	3410
							1.6	4030	2630	2150	2010	1920	1840	1750
							23	8880	5790	4740	4430	4230	4050	3850

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31		40	
420/85 R28	W15L W14L W13	450 17.72	1425 56.10	648 25.51	4224 166.3	139D/ 142A8	0.8	3570	2330	1910	1780	1700	1630	1550
							12	7860	5130	4210	3920	3740	3590	3410
							1	4030	2630	2150	2010	1920	1840	1750
							15	8880	5790	4740	4430	4230	4050	3850
							1.3	4950	3230	2640	2470	2350	2260	2150
							19	10900	7110	5810	5440	5180	4980	4740
							1.6	5590	3650	2990	2790	2660	2550	2430
							23	12310	8040	6590	6150	5860	5620	5350