

FEATURES AND BENEFITS

Directional lug
Superior traction



Robust centre
blocks

Better stability
& roadability



Wider &
flatter crown

Better floating
characteristics



Higher
rubber mass
Longer life



Rounded shoulder
Lesser damage
to soil & crop

*CTR-Low Compaction, High Traction, High Roadability

FLOATMAX FT AGRI RADIAL

WITH THE POWER OF CTR*



FLOATMAX FT

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
		mm/in	mm/in						Mixed Application					
									Static	10	30	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	6	19	25	31	40	
500/60 R22.5 FT	AG16.00	503 19.8	1172 46.1	530 20.9	3500 137.8	550	155D 155D	0.8	2880	2250	1890	1700	1510	1250
								12	6340	4960	4160	3740	3330	2750
								1.6	4490	3510	2940	2650	2360	1950
								2.3	9890	7730	6480	5840	5200	4300
								2.4	5920	4640	3890	3500	3120	2575
								3.5	13040	10220	8570	7710	6870	5670
								3.2	7480	5850	4910	4420	3930	3250
								4.6	16480	12890	10810	9740	8660	7160
								3.6	8170	6390	5360	4830	4300	3550
								5.2	18000	14070	11810	10640	9470	7820
								4	8910	6980	5850	5270	4690	3875
5.8	19630	15370	12890	11610	10330	8540								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
		mm/in	mm/in						Mixed Application					
									Static	10	30	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	Speed	bar	Static	6	19	25	31	40	
560/45 R22.5 FT	AG16.00	543 21.4	1076 42.4	493 19.4	3279 129.1	525	152D 152D	0.8	2760	2160	1810	1630	1450	1200
								12	6080	4760	3990	3590	3190	2640
								1.6	4140	3240	2720	2450	2180	1800
								2.3	9120	7140	5990	5400	4800	3960
								2.4	5430	4250	3560	3210	2860	2360
								3.5	11960	9360	7840	7070	6300	5200
								3.2	6900	5400	4530	4080	3630	3000
								4.6	15200	11890	9980	8990	8000	6610
								3.6	7480	5850	4910	4420	3930	3250
								5.2	16480	12890	10810	9740	8660	7160
								4	8170	6390	5360	4830	4300	3550
5.8	18000	14070	11810	10640	9470	7820								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		Speed	bar						Static	10	30	40	50	65
Symbol	psi	6	19	25	31	40								
560/60 R22.5 FT	AG16.00	543 21.4	1244 49.0	561 22.1	3810 150.0	600	161D 161D	0.8	3450	2700	2270	2040	1820	1500
								12	7600	5950	5000	4490	4010	3300
								1.6	5290	4140	3470	3130	2780	2300
								23	11650	9120	7640	6890	6120	5070
								2.4	7060	5530	4640	4180	3710	3070
								35	15550	12180	10220	9210	8170	6760
								3.2	8900	6970	5840	5260	4680	3870
								46	19600	15350	12860	11590	10310	8520
								4	10640	8330	6980	6290	5600	4625
								58	23440	18350	15370	13850	12330	10190
								0.8	3450	2700	2270	2040	1820	1500
								12	7600	5950	5000	4490	4010	3300
								1.8	5590	4370	3670	3300	2940	2430
								26	12310	9630	8080	7270	6480	5350
								2.8	7940	6210	5210	4690	4170	3450
								41	17490	13680	11480	10330	9190	7600
								3.8	10050	7870	6600	5940	5290	4370
								55	22140	17330	14540	13080	11650	9630
5	11500	9000	7550	6800	6050	5000								
73	25330	19820	16630	14980	13330	11010								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		Speed	bar						Static	10	30	40	50	65
Symbol	psi	6	19	25	31	40								
600/50 R22.5 FT	AG20.00	611 24.1	1172 46.1	532 20.9	3479 137.0	550	159D 159D	0.8	3220	2520	2110	1900	1690	1400
								12	7090	5550	4650	4190	3720	3080
								1.6	5010	3920	3290	2960	2640	2180
								23	11040	8630	7250	6520	5810	4800
								2.4	6670	5220	4380	3940	3510	2900
								35	14690	11500	9650	8680	7730	6390
								3.2	8400	6570	5510	4960	4420	3650
								46	18500	14470	12140	10930	9740	8040
								4	10060	7880	6610	5950	5290	4375
								58	22160	17360	14560	13110	11650	9640

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		Speed	bar						Static	10	30	40	50	65
Symbol	psi	6	19	25	31	40								
600/55 R26.5 FT	AG20.00	620 24.4	1336 52.6	608 24.0	4050 159.5	625.0	165D 165D	0.8	3800	2970	2490	2240	2000	1650
								12	8370	6540	5480	4930	4410	3630
								1.6	5910	4630	3880	3500	3110	2570
								23	13020	10200	8550	7710	6850	5660
								2.4	7710	6030	5060	4560	4050	3350
								35	16980	13280	11150	10040	8920	7380
								3.2	9780	7650	6420	5780	5140	4250
								46	21540	16850	14140	12730	11320	9360
								4	11850	9270	7780	7000	6230	5150
								58	26100	20420	17140	15420	13720	11340

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		SW	OD						Static	10	30	40	50	65
mm/in	mm/in	mm/in	6	19	25	31	40							
650/55 R26.5 FT	AG20.00	645 25.4	1389 54.7	633 24.9	4220 166.1	650	178D	0.8	5310	4160	3490	3140	2800	2310
							178D	12	11700	9160	7690	6920	6170	5090
							2	9060	7090	5950	5360	4770	3940	
							29	19960	15620	13110	11810	10510	8680	
							3	11500	9000	7550	6800	6050	5000	
							44	25330	19820	16630	14980	13330	11010	
							4	13620	10660	8940	8050	7160	5920	
							58	30000	23480	19690	17730	15770	13040	
							5	15500	12130	10180	9170	8160	6740	
							73	34140	26720	22420	20200	17970	14850	
							6.0	17250	13500	11330	10200	9080	7500	
87	38000	29740	24960	22470	20000	16520								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		SW	OD						Static	10	30	40	50	65
mm/in	mm/in	mm/in	6	19	25	31	40							
710/50 R26.5 FT	AG20.00	710 28.0	1383 54.4	628 24.7	4171 164.2	650.0	170D	0.8	5360	4190	3520	3170	2820	2330
							170D	12	11810	9230	7750	6980	6210	5130
							1.6	8070	6320	5300	4770	4250	3510	
							23	17780	13920	11670	10510	9360	7730	
							2.4	10240	8010	6720	6050	5380	4450	
							35	22560	17640	14800	13330	11850	9800	
							3.2	12120	9490	7960	7170	6380	5270	
							46	26700	20900	17530	15790	14050	11610	
							4	13800	10800	9060	8160	7260	6000	
							58	30400	23790	19960	17970	15990	13220	

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		Speed, km/h (mph)												
		Mixed Application												
		SW	OD						Static	10	30	40	50	65
mm/in	mm/in	mm/in	6	19	25	31	40							
710/45 R22.5 FT	AG24.00	745 29.3	1209 47.6	541 21.3	3661 144.2	575	165D	0.8	4620	3620	3040	2730	2430	2010
							165D	12	10180	7970	6700	6010	5350	4430
							1.8	7430	5810	4880	4390	3910	3230	
							26	16370	12800	10750	9670	8610	7110	
							2.6	9200	7200	6040	5440	4840	4000	
							38	20260	15860	13300	11980	10660	8810	
							3.4	10760	8420	7070	6360	5660	4680	
							49	23700	18550	15570	14010	12470	10310	
							4	11850	9270	7780	7000	6230	5150	
							58	26100	20420	17140	15420	13720	11340	

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
									Speed, km/h (mph)					
		SW	OD						Mixed Application					
		mm/in	mm/in						mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
650/65 R26.5 FT	AG20.00	650 25.6	1518 59.8	687 27.1	4597 181.0	725	174D 174D	0.8	6000	4700	4120	3550	3160	2610
								12	13220	10350	9070	7820	6960	5750
								1.6	9020	7060	6190	5330	4740	3920
								23	19870	15550	13630	11740	10440	8630
								2.4	11430	8950	7850	6760	6010	4970
								35	25180	19710	17290	14890	13240	10950
								3	13020	10190	8940	7700	6850	5660
								44	28680	22440	19690	16960	15090	12470
								3.6	14490	11340	9950	8570	7620	6300
								52	31920	24980	21920	18880	16780	13880
								4.0	15410	12060	10590	9110	8110	6700
58	33940	26560	23330	20070	17860	14760								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
									Speed, km/h (mph)					
		SW	OD						Mixed Application					
		mm/in	mm/in						mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
650/65 R30.5 FT	AG20.00	645 25.4	1621 63.8	726 28.6	4909 193.3	775	176D 176D	0.8	6370	4990	4380	3770	3350	2770
								12	14030	10990	9650	8300	7380	6100
								1.6	9570	7490	6570	5660	5030	4160
								23	21080	16500	14470	12470	11080	9160
								2.4	12120	9490	8330	7170	6380	5270
								35	26700	20900	18350	15790	14050	11610
								3	13800	10800	9480	8160	7260	6000
								44	30400	23790	20880	17970	15990	13220
								3.6	15360	12020	10550	9080	8080	6680
								52	33830	26480	23240	20000	17800	14710
								4.0	16330	12780	11220	9660	8590	7100
58	35970	28150	24710	21280	18920	15640								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
									Speed, km/h (mph)					
		SW	OD						Mixed Application					
		mm/in	mm/in						mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
650/60 R26.5 FT	AG20.00	650 25.6	1453 57.2	656 25.8	4291 168.9	700	173D 173D	0.8	5820	4550	4000	3440	3060	2530
								12	12820	10020	8810	7580	6740	5570
								1.6	8740	6840	6000	5170	4600	3800
								23	19250	15070	13220	11390	10130	8370
								2.4	11090	8680	7620	6560	5830	4820
								35	24430	19120	16780	14450	12840	10620
								3	12630	9880	8670	7470	6640	5490
								44	27820	21760	19100	16450	14630	12090
								3.6	14050	11000	9650	8310	7390	6110
								52	30950	24230	21260	18300	16280	13460
								4.0	14950	11700	10270	8840	7870	6500
58	32930	25770	22620	19470	17330	14320								

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
									Mixed Application					
									Static	10	25	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	bar	psi	6		15	25	31	40	
750/45 R26.5 FT	AG24.00	754 29.7	1355 53.3	616 24.3	4001 157.5	650	170D 170D	0.8	4490	3510	3080	2650	2360	1950
								12	9890	7730	6780	5840	5200	4300
								1.6	7060	5530	4850	4180	3710	3070
								23	15550	12180	10680	9210	8170	6760
								2.4	9200	7200	6320	5440	4840	4000
								35	20260	15860	13920	11980	10660	8810
								3	10930	8550	7510	6460	5750	4750
								44	24070	18830	16540	14230	12670	10460
								3.6	12540	9810	8610	7410	6590	5450
								52	27620	21610	18960	16320	14520	12000
								4.0	13800	10800	9480	8160	7260	6000
								58	30400	23790	20880	17970	15990	13220

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
									Mixed Application					
									Static	10	25	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	bar	psi	6		15	25	31	40	
750/60 R30.5 FT	AG24.00	754 29.7	1680 66.1	759 29.9	4961 195.3	800	181D 181D	0.8	6140	4810	4220	3630	3230	2670
								12	13520	10590	9300	8000	7110	5880
								1.6	9640	7540	6620	5700	5070	4190
								23	21230	16610	14580	12560	11170	9230
								2.4	12740	9970	8750	7530	6700	5540
								35	28060	21960	19270	16590	14760	12200
								3	15020	11750	10320	8880	7900	6530
								44	33080	25880	22730	19560	17400	14380
								3.6	17410	13630	11960	10300	9160	7570
								52	38350	30020	26340	22690	20180	16670
								4.0	18980	14850	13040	11220	9980	8250
								58	41810	32710	28720	24710	21980	18170

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
									MIXED APPLICATION					
									Static	10	30	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	bar	psi	6		19	25	31	40	
710/50 R30.5 FT	AG20.00, AG24.00	715 28.1	1485 58.5	679 26.7	4385 172.7	700	173D 173D	0.8	4620	3620	3180	2730	2430	2010
								12	10180	7970	7000	6010	5350	4430
								1.6	7290	5710	5010	4310	3840	3170
								23	16060	12580	11040	9490	8460	6980
								2.4	9940	7780	6830	5880	5230	4320
								35	21890	17140	15040	12950	11520	9520
								3.2	12370	9680	8500	7320	6510	5380
								46	27250	21320	18720	16120	14340	11850
								4	14950	11700	10270	8840	7870	6500
								58	32930	25770	22620	19470	17330	14320

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
									Mixed Application					
									mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
6	19	25	31	40										
Symbol	psi													
800/60 R32	AG27.00, AG25.00, AG28.00	800 31.5	1800 70.9	812 32.0	5316 209.3	850	185D 185D	0.8	4620	3620	3180	2730	2430	2010
								12	10180	7970	7000	6010	5350	4430
								1.6	7290	5710	5010	4310	3840	3170
								23	16060	12580	11040	9490	8460	6980
								2.4	9940	7780	6830	5880	5230	4320
								35	21890	17140	15040	12950	11520	9520
								3.2	12370	9680	8500	7320	6510	5380
								46	27250	21320	18720	16120	14340	11850
								4	21280	16650	14620	12580	11190	9250
								58	46870	36670	32200	27710	24650	20370