

# FEATURES AND BENEFITS

Rounded shoulder  
Reduced damage  
to crops



Larger volume  
& footprint

Reduced  
compaction

## FLOTATION PLUS

TRA CODE : IND-X

Size	Rim Width in	Unloaded dimension		Static Circumference	Rolling Circumference	PR	Infl. press	Load Carrying Capacity		
		SW	OD					Max Speed	Max Load	Max Load
		mm/in	mm/in						(Free Rolling)	(Drive wheel)
				mm/in	mm/in		Bar	kmph	kg	kg
				mm/in	mm/in		Psi	mph	lbs	lbs
500/50-17	16.00 DC	500	950	445	2850	14 PR	2.8	40	3250	2240
		19.7	37.4	17.5	112.2		41	25	7165	4938
480/45-17	16.00 DC	490	866	405	2598	18 PR TL	3.3	40	3150	2240
		19.3	34.1	16.0	102.3	148A8 FR 136A8 DW	48	25	6940	4940
480/45-17	16.00 DC	490	866	405	2598	16 PR	3.2	40	3000	2120
		19.3	34.1	16.0	102.3	146A8 FR & 134A8DW	46	25	6614	4674
480/45-17	16.00 DC	490	866	405	2598	14 PR	2.8	40	2800	1950
		19.3	34.1	16.0	102.3	144 A8 FR / 131 A8 DW	41	25	6170	4300
480/45-17	16.00 DC	490	866	405	2598	10 PR	2.25	40	2360	
		19.3	34.1	16.0	102.3	138 A8	32	25	5205	