

FEATURES AND BENEFITS

R4 tread pattern
Suitable on & off
the road



Strong nylon casing
Capable to run at
high speeds

Superior compound
Designed for crane
& rescue vehicles



Tough wide base
Excellent traction &
handling response

LOADER XL

TRA CODE : G2/L2

Size	PR	Type	Rim Width in	Flange Height in	SW	OD	Static Loaded Radius	Rolling Circum	Grader Service		Loader Service							
									40kmph / (25mph)		10kmph / (5mph)							
									Max load	Infl. Prs.	Max load	Infl. Prs.						
									kg	bar	kg	bar						
									lbs	psi	lbs	psi						
20.5-25	16	TL	17	2.0	520 21	1492 59	686 27	4416 174	4000	2.25	8250	3.5						
									8800.0	33	18200	51						
	12	TL							3550	1.75	6700	2.5						
									7850	25.0	14800	36						
17.5-25	24	TL	14	1.5	445 17.5	1348 53.1	614 24.2	3990 157.1	6000	5	9250	6.75						
									13220	73	20390	98						
17.5-25	16	TL							14	1.5	445 18	1348 53	614 24	3990 157	3350	3.0	7300	4.7
															7400.0	43	16100	69
12	TL	2900	2.0	6150	3.5													
		6400	29.0	13600	51													
15.5-25	12	TL	12.00	1.3	394 16	1278 50	594 23	3780 149	2650	2.5	5600	4.0						
									5840	36.0	12345	58						