

FEATURES AND BENEFITS

Greater lug overlaps
and more lugs in
footprint



Uniform load
distribution

Extra reinforced
Sidewalls

Additional lateral
stability



Strong bead

Better carcass
strength and load
carrying capacity

LOAD PRO

TRA CODE : R-4

Size	Type	PR	Rim	Unloaded dimension		SLR	RC	LI/SS	In. Press	Max. speed	Max. load
				OD	SW						
				mm/in	mm/in						
				1425	450						
440/80-28	TL	14	W15L x 28	56.1	17.7	638	4305	156 A8	3.2	40	4000
						25.1	169.5		46	25	8820

Size	Type	Rim	Outer	Section	Static	Rolling	PR	Load Index	Inflation	Max.	Load
			Outer	Section	Loaded	Circum-					
			mm/in	mm/in	Radius	ference					
			1330	441	600	3940					
440/80-24	TL	W15L	52.3	17.3	23.6	155	168 A8	5.00	40	5600	
									72.5	25	12346

Size	Type	Rim	Outer	Section	Static	Rolling	PR	Load Index	Inflation	Max.	Load
			Diameter	Width	Loaded	Circum-					
			mm/in	mm/in	Radius	ference					
			1275	420	580	3800					
400/80-24	TL	W13L	50	16.5	22.8	149.6	162 A8	5	40	4750	
									73	25	10472