

# FEATURES AND BENEFITS



## MPT 602

TRA CODE : IND-X

Size	Rim Width in	Unloaded dimension		Static Loaded Radius	Rolling Circum	PR	Load carrying capacity			
		SW	OD				Infl Pressure bar / (psi)	Load Index & Speed Symbol	Max Speed (kmph) / (mph)	Max Load kgs/ (lbs)
		mm/in	mm/in							
405/70-24 (16.0/70-20)	13.00	405	1186	547	3535	16	4.5	156 B	50	4000
		15.9	46.7	21.5	139.2		65		31	8818
405/70-24 (16.0/70-20)	13.00	405	1186	547	3535	14	4	151 D	65	3450
		15.9	46.7	21.5	139.2		58		40	7606
405/70-20 (16.0/70-20)	13.00	405	1085	505	3225	20	6.5	170 B	50	6000
		15.9	42.7	19.9	127.0		94		31	13220
405/70-20 (16.0/70-20)	13.00	405	1080	505	3190	18	5.75	165 B	50	5150
		15.9	42.5	19.9	125.6		83		31	11354
405/70-20 (16.0/70-20)	13.00	405	1085	505	3225	14	3.5	149 B	50	3250
		15.9	42.7	19.9	127.0		51		31	7165
12.5-20	11.0	1042	325	480	3065	12	3.5	135 D	65	2180
		41.0	12.8	18.9	120.7		51.0		40.0	4795
10.00-20	7.50	280	1075	509	3255	16	7.5	146	50	3000
		11.0	42.3	20.0	128.1		109	B	31	6610
12.5-18	11.0	990	325	455	2910	16	5.0	144 D	65	2800
		39.0	12.8	17.9	114.6		73.0		40.0	6175
12.5-18	11.0	990	325	455	2910	12	3.5	134 D	65	2120
		39.0	12.8	17.9	114.6		51.0		40.0	4665