

FEATURES AND BENEFITS

Strong nylon casing
Higher strength
and stability

Specially designed
wide lugs
Better self-cleaning



Superior tread
compound
Resistance to tearing
& cracking

MPT 808

TRA CODE : IND-X

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in			bar	Kmph	kg
								psi	mph	lbs
14.5-20	143 B	14	11x20	355	1098	505	3260	3.5	50	2725
				14	43.2	19.9	128.3	51	30	6010

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in			bar	Kmph	kg
								psi	mph	lbs
12.5-20	140 B	12	11x20	325	1040	475	3090	4	50	2500
				12.8	40.9	18.7	121.7	58	30	5510

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in			bar	Kmph	kg
								psi	mph	lbs
10.5-20	135 B	12	9x20	270	955	445	2880	4.3	50	2180
				10.6	37.6	17.5	113.4	62	30	4810

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs
18-19.5	165 B	18	11x20	457	1110	503	3227	7.25	50	5150
				18	44	20	127	105	30	11354

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs
12.5-18	135 B	12	11x20	325	990	450	2940	3.5	50	2180
				12.8	39	17.7	115.7	51	30	4810

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs
12.0-18	145 A6	12	W9x18	295	930	430	2775	4.5	30	2900
				11.6	36.6	16.9	109.2	65	19	6395

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs
12.0/75-18 (300/75-18)	139 A8 (FR) /126 A8 (DW)	12	W9x18	295	915	427	2755	4	40	2430 / 1700
				11.6	36.1	16.8	108.4	58	25	5355 / 3745

Size	Load Index Speed Symbol	PR	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Recommended load, kg (lbs) Infl. Press.	Speed, km/h (mph)	Load carrying capacity			
				SW	OD						bar	Kmph	KG
				mm/in	mm/in								
10.5-18	134B	12	9 x 18	270	905	400	2690	4.5	50	2120			
				10.6	35.6	15.7	105.9	65	31	4670			

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs (FR / DW)
11.5/80-15.3	139 A8 (FR)/ 126 A8 (DW)	14	9x15.3	292	870	395	2580	4.75	40	2430 / 1700
				11.5	34.3	15.6	101.6	69	25	5355 / 3745

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in					
								psi	mph	lbs (FR / DW)
10.0/75-15.3	130 A8 (FR)/ 118 A8 (DW)	14	9x15.3	260	775	365	2400	5.5	40	1900 / 1320
				10.2	30.5	14.4	94.5	79	25	4190 / 2910