

FEATURES AND BENEFITS

Reinforced Sidewall
Long service life



Specially formulated
tread compound
Improved penetration and
heat resistance



Flatter & larger
tread width

Higher ground contact
area & traction



*CTR-Low Compaction, High Traction, High Roadability

SLICK-404

TRA CODE : L5S

| Size | PR | Type | Rim Width in | Flange Height in | Unloaded Dimension | | Static Loaded Radius | Rolling Circum | Load Capacity | | | |
|----------|----|------|-----------------|---------------------|--------------------|-------|----------------------|----------------|---------------|------------------|-------------------|-------------------|
| | | | | | SW | OD | | | Infl. Prs. | 10 kmph / (5mph) | 15 kmph / (10mph) | 25 kmph / (15mph) |
| | | | | | mm/in | mm/in | | | | Max Load | Max Load | Max Load |
| | | | | | mm/in | mm/in | | | | bar | kg | kg |
| | | | | psi | lbs | lbs | lbs | | | | | |
| 17.5-25 | 20 | TL | 14 | 1.5 | 445 | 1399 | 648 | 4141 | 5.75 | 8250 | 7180 | 6600 |
| | | | | | 18 | 55 | 26 | 163 | 83 | 18200 | 15830 | 14550 |
| 17.5-25 | 24 | TL | 14 | 1.5 | 445 | 1399 | 648 | 4141 | 5.75 | 9825 | 8567 | 7860 |
| | | | | | 18 | 55 | 26 | 163 | 83 | 21664 | 18891 | 17331 |
| 18.00-25 | 32 | TL | 13 | 2.5 | 498 | 1673 | 768 | 4952 | 7.5 | 15000 | 13050 | 12000 |
| | | | | | | | | | 109 | 33100 | 28770 | 26455 |
| | 40 | | | | 20 | 66 | 30 | 195 | 9.5 | 17000 | 14790 | 13600 |
| | | | | | | | | | 138 | 37480 | 30605 | 29980 |
| 12.00-20 | 20 | TT | 8.5 | - | 315 | 1163 | 538 | 3433 | 7.75 | 6000 | 5220 | 4800 |
| | | | | | 12 | 46 | 21 | 135 | 112 | 13230 | 11510 | 10580 |
| 12.00-24 | 20 | TT | 8.5 | - | 310 | 1270 | 592 | 3759 | 8.25 | 6900 | 6000 | 5520 |
| | | | | | 12 | 50 | 23 | 148 | 120 | 15210 | 13230 | 12170 |
| 12.00-24 | 24 | TT | 8.5 | - | 310 | 1270 | 592 | 3759 | 9.75 | 7650 | 6656 | 6120 |
| | | | | | 12 | 50 | 23 | 148 | 141 | 16868 | 14675 | 13495 |
| 14.00-24 | 28 | TT | 10 | - | 375 | 1418 | 658 | 4197 | 10 | 15625 | 13625 | 12500 |
| | | | | | 15 | 56 | 26 | 165 | 145 | 34453 | 30043 | 27563 |