

# FEATURES AND BENEFITS

Stepped  
sidewall design

Improved performance  
on slopes



Special tread  
compound

For longer life

Tie bar at the center

Strengthened lug base  
for better stability



Buttressed  
bar base

Better  
self-cleaning



23° Tread Bars

Best in class traction



Stronger carcass

To carry

heavier loads



\*Read more about warranty policy on page 89

## YIELDMAX 23°

WITH THE POWER OF CTR\*



# YIELDMAX 23°

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm/in	mm/in					Static	30	40
									19	25
30.5L-32	DW 27A	785	1825	830	5560	14 PR	1.5	9000	5000	4500
		30.9	71.9	32.7	218.9	160A8	22	19840	11020	9920

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm/in	mm/in					Static	30	40
									19	25
24.5-32	DW21B	625	1825	830	5560	12 PR 156A8	1.7	8000	4375	4000
		24.6	71.9	32.7	218.9		25	17630	9640	8820

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm/in	mm/in					Static	30	40
									19	25
28L-26	DW 25A	730	1630	750	4970	12PR	1.4	6700	3720	3350
		28.7	64.2	29.5	195.7	150A8	20	14770	8200	7380

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm/in	mm/in					Static	30	40
									19	25
30.5L-32	DW21B	775	1819	820	5540	12 PR 162A6/	1.4	8500	4750	4250
		30.5	71.6	32.3	218.1	158A8	20	18730	10470	9370

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm/in	mm/in					Static	30	40
									19	25
24.5-32	DW21B	622	1803	820	5490	10 PR	1.4	7100	3875	3550
		24.5	71.0	32.3	216.1	155A6/152A8	20	15650	8540	7820