

# FLOATMAX RT

**FEATURE**  
Directional Lug

**BENEFIT**  
Higher traction,  
Comfortable ride

**FEATURE**  
Robust Centre Blocks

**BENEFIT**  
Low noise and smooth  
run on hard surface

**FEATURE**  
Steel belted radial  
construction

**BENEFIT**  
Protection from  
Punctures



**FEATURE**  
Rounded Shoulder

**BENEFIT**  
Less damage to  
soil & crops


**FEATURE**  
Interconnected  
grooves

**BENEFIT**  
Better self cleaning  
properties

**FEATURE**  
Flatter Crown width

**BENEFIT**  
Larger footprint,  
lower compaction

## MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)						
		SW mm in	OD mm in	Radius mm in	mm in	Speed Symbol		bar psi	Static	Speed, km/h (mph)				
										MIXED APPLICATION				
		10 6	30 19	40 25	50 31	65 40								
580 65R22.5 RT	AG16.00	577 22.7	1318 51.9	601 23.7	3996 157.3	166D 166D	0.8	4760	3730	3130	2820	2500	2070	
							12	10480	8220	6890	6210	5510	4560	
							1.6	7130	5580	4680	4220	3750	3100	
							23	15700	12290	10310	9300	8260	6830	
							2.4	9040	7070	5930	5340	4760	3930	
							35	19910	15570	13060	11760	10480	8660	
							3.2	10700	8370	7020	6320	5630	4650	
							46	23570	18440	15460	13920	12400	10240	
							4	12190	9540	8000	7210	6410	5300	
58	26850	21010	17620	15880	14120	11670								

\* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards