

# FLOTATION T422



**FEATURE**

- Tough nylon casing  
Strong brad buldle

**BENEFIT**

- High load carrying capacity

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to crops


**FEATURE**

- Larger volume and footprint

**BENEFIT**

- Reduced compaction

**MACHINERY**



Trailer

| Size        | PR    | Rim Width<br>in | Unloaded dimension |                | Static Circumference<br>mm<br>in | Rolling Circumference<br>mm<br>in | Infl. press.<br>Bar<br>Psi | Load Carrying Capacity |             |                      |                                      |                                     | Tread Depth<br>mm<br>in |
|-------------|-------|-----------------|--------------------|----------------|----------------------------------|-----------------------------------|----------------------------|------------------------|-------------|----------------------|--------------------------------------|-------------------------------------|-------------------------|
|             |       |                 | SW<br>mm<br>in     | OD<br>mm<br>in |                                  |                                   |                            | Load, Speed Symbol     |             | Speed<br>kmph<br>mph | Max Load (Free Rolling)<br>kg<br>lbs | Max Load (Drive wheel)<br>kg<br>lbs |                         |
|             |       |                 |                    |                |                                  |                                   |                            | Free Rolling           | Drive Wheel |                      |                                      |                                     |                         |
|             |       |                 |                    |                |                                  |                                   |                            |                        |             |                      |                                      |                                     |                         |
| 700/50-26.5 | 12 PR | 24.00 DC        | 700                | 1333           | 585                              | 3986                              | 1.8                        | 169 / 165              | 157 / 154   | 40                   | 5800                                 | 4125                                | 24                      |
|             |       |                 |                    |                |                                  |                                   | 26                         | A8 / B                 | A8 / B      | 25                   | 12787                                | 9094                                | 0.9                     |
|             | 16 PR |                 | 27.6               | 52.5           | 23.0                             | 156.9                             | 2.4                        | 174 / 170              | 162 / 158   | 40                   | 6700                                 | 4750                                | 24                      |
|             |       |                 |                    |                |                                  |                                   | 35                         | A8 / B                 | A8 / B      | 25                   | 14771                                | 10472                               | 0.9                     |