

LOADPRO BL

FEATURE

Non-directional

BENEFIT

For better traction and strong grip

FEATURE

Center of tie bar

BENEFIT

Outstanding comfort

FEATURE

Sharp shoulder

BENEFIT

More contact area



FEATURE

Extra reinforced Sidewall

BENEFIT

Additional strength prevents stub penetration

FEATURE

Higher base width

BENEFIT

Better road ability and high traction


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity & Better fitment

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius				Speed, km/h (mph)				Cyclic operation			
		mm	mm	mm	mm	Speed	bar	Constant load				10	15		
		in	in	in	in	Symbol	psi	Static	10	20	30	40	50	10	15
460/ 70R24	W15L	455	1254	566	3713	159 A8/B	1.6	5890	3200	2790	2660	2560	2560	3840	3430
							23	12970	7050	6150	5860	5640	37120	8460	7560
	W16L	17.9	49.4	22.3	146		2.4	7450	4050	3530	3370	3240	3240	4860	4340
							35	16410	8920	7780	7420	7140	46980	10700	9560
	W16L	17.9	49.4	22.3	146		3.0	8490	4610	4020	3840	3690	3690	5540	4940
							44	18700	10150	8850	8460	8130	53505	12200	10880
							3.6	9450	5140	4480	4270	4110	4110	6170	5510
							52	20810	11320	9870	9410	9050	59595	13590	12140
							4	10060	5470	4770	4550	4375	4375	6560	5860
							58	22160	12050	10510	10020	9640	63437.5	14450	12910