

TYROCK XL

TRA CODE: R4

FEATURE

- Special stone ejector between lugs

BENEFIT

- Avoid stone trapping and puncture

FEATURE

- Specially designed tread pattern

BENEFIT

- Superior traction



FEATURE

- Strong nylon casing & special industrial tread compound

BENEFIT

- Higher mileage

MACHINERY



Backhoe Loader

Size	Type	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Capacity									
					SW	OD			Industrial Use				Agriculture Use					
									Infl. Press	Constant Load		Cyclic application		Infl. Press	Road Transport			
					Speed Km/h/mph					Speed Km/h/mph								
					bar	20			40	20	40	bar	20	40				
psi	12	25	12	25	psi	12	25											
									Recommended load kg/lbs									
									Recommended load Kg/lbs									
16.9-28	TT	152 A8	12	W15L	440	1430	650	4233	2.3	3600	3300	4060	3300	2.1	3380	2520		
					17.3	55.6			25.6	166.7	33	7930	7270	8940	7270	30	7440	5550
					2.4	3700			3390	4170	3390	2.2	3470	2590				
					35	8150			7470	9190	7470	32	7640	5700				
					2.6	3870			3550	4370	3550	2.4	3650	2725				
					38	8520			7820	9630	7820	35	8040	6000				

Also available in sizes: 19.5L-24*

All tires confirms ETRTO T&RA & STRO standards